

SERVO HMT GEAR OIL 90

GRADES AVAILABLE - SERVO HMT GEAR OIL 90

DESCRIPTION

Servo HMT Gear oil is extreme pressure automotive gear lubricants. These oils are blended from selected base stocks and contain additives to provide extreme pressure, anti-rust-corrosion characteristics

APPLICATION

Servo HMT Gear oil is recommended as gear lubricant for HMT Tractors. Servo HMT Gear is specially designed for power transmission units and moving equipments of Tractors.

PERFORMANCE BENEFITS

Servo HMT Gear oils

- Satisfy the lubrication requirements of a wide variety of gears.
- Provide protection against wear, due to good EP characteristics
- Give long service life even under high temperature operation since it has excellent oxidation stability
- Provide good protection against corrosion

PERFORMANCE STANDARDS

Servo HMT Gear oil meets:

- API Service GL 4
- IS: 1118-1957 (Reaffirmed 1993)
- UK Defence CS 3000A
- US military MIL-L-2105

MANUFACTURERS APPROVAL

Approved as Genuine oil for HMT Tractors.

CHARACTERISTICS

SAE GRADE	HMT Gear
Kinematic Viscosity cSt @ 100°C	16-18
Viscosity Index, Min.	90
Flash point (COC), °C Min.	180
Pour Point, °C Max.	(-) 9

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR :

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai – 400 051

E-Mail: tsservices@indianoil.co.in OR tech_services@indianoil.co.in

