## Schedule - I

## Format for declaring capacity of Pipeline

- 1) Name of entity: IndianOil corporation limited
- 2) Name of Pipeline: Dadri Panipat R-LNG Pipeline (DPPL)
- 3) Section wise capacity of pipeline ( to be furnished for each section separately ):
  - a) Number of sections: One (01)
  - b) Name of Section with start and end point: Dadri to Panipat section (Dadri as start point and Panipat as end point)
  - c) Capacity (i) Volume terms : 9.5 MMSCMD
    - (ii) Energy terms: 372460.317 MMBTU/day (calculated at standard GCV i.e. 9880 KCcal/SCM)
- 4) Number of AHAs: One (01)
- 5) Number of entry points and pipeline route: One (01) , Dadri (UP) to Panipat(Haryana) route
- 6) Location of entry points: GAIL Dadri (UP Dadri )
- 7) Number of exit points: Nine (09)
- 8) Location of exit points:
  - i. Panipat Refinery (Haryana),
  - ii. Panipat Naptha Cracker (Haryana),
  - iii. NFL Panipat at Ch. 113.1 Km (Haryana),
  - iv. IVL Karnal at Ch. 132 Km(Haryana),
  - v. CGD Panipat(IOAGPL) at Ch. 105.97 Km (Harvana).
  - vi. CGD Karnal/Kaithal(IGL) at Ch. 132 Km(Haryana),
  - vii. NTPC Dadri at Ch. 0.0 Km(Haryana),
  - viii. CGD Baghpat (BGEPL) at Ch. 62.8 Km (Uttar Pradesh)
  - ix. CGD Sonipat (HPCL) at Ch. 92.75(Haryana),
- Entry point wise capacity(to be furnished separately for each entry point): Single entry point from Dadri (UP) with skid capacity of 10 MMSCMD
- 10) Exit point wise capacity (to be furnished separately for each exit point):
  - I) Panipat Refinery Skid Capacity: 4.3 MMSCMD
  - II) Panipat Naptha Cracker Skid Capacity: 1.5 MMSCMD
  - III) NFL Panipat Skid Capacity: 1.5 MMSCMD
  - IV) IVL Dhunseri Skid Capacity: 0.08 MMSCMD
  - V) CGD Panipat(IOAGPL) skid Capacity: 0.288 MMSCMD
  - VI) CGD Karnal/Kaithal(IGL) skid Capacity: 0.24 MMSCMD
  - VII) CGD Baghpat (BGEPL) skid Capacity: 0.312 MMSCMD
  - VIII) NTPC Dadri Skid Capacity: 1.0 MMSCMD
    IX) CGD Sonipat (HPCL): 0.17 MMSCMD
- 11) Technical parameter:
  - a) Inlet pressure at entry point: 52.78-53.28 kg/cm2
  - b) Calorific value band at entry point: 9200 9800 Kcal /SCM (Gross Calorific Value Band)
  - c) Temperature: 31.64 39.89 DegC
  - d) Other elements as per Schedule -II:

Carbon Di-oxide (mole % max): 0.0313 Mole %

Nitrogen (mole % max): 0.4673 Mole %

Temperature (Degree Celsius, max): 32 DegC

- \*Rest parameters (mentioned in Schedule II) are not being analysed by GC at Panipat
- 12) Status for the extra capacity available in pipeline system on common carrier basis: 2.375 MMSCMD Available
- 13) Details of the common carrier capacity being used by transporter itself or on contract carrier basis: NIL
- 14) Any demand pending with the transporter for common carrier usage of pipeline along with duration of such pendency: NIL
- 15) Preferences on entry and exit points: NIL

(Mayank Khare)
Chief Operation Manager
Northern Region Pipelines, Panipat