SCHEDULE - I

Format for declaring capacity of Pipeline (See regulation 4(2))

1. Name of entity: Indian Oil Corporation Limited

2. Name of pipeline: Devanagonthi Devanahalli ATF Pipeline

3. Details of capacity of Pipeline (as per table below):

	Capacity approved byPNGRB		Break up of capacity for period (MMT)				
Name of Section	Total Including Common carrier (MMT)	Common Carrier (MMT)	Own Requirement*	Firmed-up contracted capacity with other entitiesfor a period of at least one year		Common Carrier Capacity with other entities for a period of less than one year	
				Contracted	Available	Contracted	Available
Devanagonthi - Devanahalli	0.66	0.16	0.44	NIL	NIL	0.16	NIL

^{*} FY 2023-24

- 4. Number of entry points on the pipeline route: 1
- 5. Location of entry points: IOCL Devanagonthi Terminal
- 6. Number of exit points: 1
- 7. Location of exit points: Devanahalli (Bengaluru Airport)
- 8. Technical parameters:
 - a) Inlet pressure at entry point: As per operational requirements
 - b) Grade band at entry point: As per AQCAM 2016
 - c) Temperature: Max 45 deg. C
 - d) Other elements as per Schedule II: As per Schedule-II
- 14. Any demand pending with the transporter for common carrier usage of the pipeline along with duration of such pendency: **Not Applicable**
- 15. Preference on entry and exit points:

a) Entry Point: - Devanagonthi

b) Exit Points: - Devanahalli

Petroleum Product Physical Characteristics Specifications

For Motor Spirits (Euro VI)		For High Speed Diesel (Euro VI)		
Parameter		Parameter		
Sulphur (Maximum ppm)		DENSITY @ 15 deg.C, KG/M3		
Research Octane Number (RON) (Minimum)		SULPHUR, PPM (Maximum)	Limit as per latest IS:1460	
Benzene, Vol % (Maximum)	Limit as per latest IS:2796	DISTILLATION 95% Recovery oC (Maximum)		
Aromatics, Vol% (Maximum)		CETANE NO. (Minimum)		
Olefins, Vol% (Maximum)		WATER CONTENT (% by Vol) (Maximum)		
Motor Octane Number		Polycyclic Aromatic Hydrocarbon	1	
(MoN) (Minimum)		(PAH) wt (%)		
Reid Vapour Pressure (RVP)		Any other parameter		
kPa) (Maximum)		(limits as per IS standards)		
Any other parameter				
(limits as per IS standards)				

(C) For other Petroleum Products							
Products	Specific Gravity (at 15°C)	Viscosity (CST)	Vapour Pressure (Kg/sq.cm)				
Liquefied Petroleum Gas (LPG) As per latest IS:4576	Not Applicable						
Superior Kerosene Oil (SKO) As per latest IS:1459	As per latest IQCM						
Aviation Turbine Fuel(ATF) As per latest IS:1571	As per latest AQCAM						
NAPTHA As per latest IQCM	Not Applicable						