



General Purpose Machinery Oils

Product	Kin. Viscosity cSt at 40 °C	Pour Point °C, Max.	Flash Point COC, °C Min.	Description / Application
Lubrex 22	20 – 24	-	150	<p>Lubrex oils are normally recommended for non-critical all loss lubrication systems and hand oiling applications involving lubrication of bearings, open gears, lightly loaded slides and guide ways of machine tools. Lubrex oils of appropriate viscosity are widely used in textile mills for lubrication of looms and other equipments, which do not require additive treated oils. These oils can also be used as fluid sealing medium for gas holder where the gases do not react with mineral oils and as filter media in oil-bath type air cleaners. Lubrex 22 is recommended for flushing of automotive and industrial equipments. The characteristics of Lubrex 22 make it possible to easily clean all inaccessible internal surfaces of various equipments.</p>
Lubrex 32	29 – 35	-	150	
Lubrex 46	42 – 50	-	160	
Lubrex 57	54 – 60	-	160	
Lubrex 68	62 – 74	-	160	
Lubrex 100	90 – 110	-	170	
Lubrex 150	135 – 165	-	204	
Lubrex 220	198 – 242	-	220	
Lubrex 320	288 – 352	-	220	
Lubrex 460	414 – 506	-	240	

