SERVO[®] product data sheet SERVO PRIDE SUPER



GRADES AVAILABLE – SERVO PRIDE SUPER 15W-40, 20W-50

DESCRIPTION	APPLICATION	
Servo Pride Super 15W-40 is a premium quality "Super High Performance Diesel Engine Oil" (SHPDO). It is blended with high quality base stocks and carefully selected additives to meet the stringent requirements of various OEMs.	Servo Pride Super 15W-40 is recommended for all types of diesel powered vehicles ranging from light commercial vehicles to heavy duty turbo charged diesel engines and also suitable for off-highway equipment and power generation sets operating on high speed diesel.	
PERFORMANCE BENEFITS	PERFORMANCE STANDARDS	
 Increased oil drain period with potential of 45,000 kms under ideal operating conditions. Enhanced engine life Ensures increased engine cleanliness Reduced wear All weather oil Low oil top up 	 ACEA - E5 - 02 E-DL 4 OF IS:13656-1993 MB 228.3 	

CHARACTERISTICS

SAE GRADE	15W-40	20W-50
Kinematic Viscosity @ 100°C, cSt	13.5 – 15.5	16.3 – 17.3
Viscosity Index, Min	135	125
Flash Point, COC, °C, Min	200	200
TBN, mg, KOH/gm	14 - 16	14 - 16

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR : Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai – 400 051 E-Mail: tservices@indianoil.co.in OR tech_services@indianoil.co.in