SERVO[®] product data sheet SERVO GEAR SUPER ALT 85W-140



GRADES AVAILABLE - SERVO GEAR SUPER ALT 85W-140

DESCRIPTION	APPLICATION
Servo Gear Super ALT 85W-140 oil is an extreme pressure automotive gear lubricant. This oil is blended from selected base stocks and contain specific additive package to provide extreme pressure, anti-rust-corrosion characteristics. This formulation is specially developed for hypoid type rear axles of Ashok Leyalnd vehicles.	Servo Gear Super ALT 85W-140 oil is recommended for hypoid type of rear axle of Ashok Leyland vehicles.
	PERFORMANCE STANDARDS
 PERFORMANCE BENEFITS Provide protection against wear, due to good EP characteristics Give long service life even under high temperature operation since it has excellent oxidation stability. Provide good protection against corrosion. Keep the differentials clean and free of deposits. 	 Servo Gear Super ALT 85W-140 meets API Service GL 5 US military MIL-L-2105D APPROVAL Ashok Leyland Ltd., Chennai for every 48000 KMs.

CHARACTERISTICS

SAE GRADE	ALT 85W-140
Kinematic Viscosity cSt @ 100°C	28 – 32
Viscosity Index, Min.	90
Flash point (COC), °C Min.	180
Pour Point, °C Max.	(-) 18

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd.,G-9,Ali Yavar Jung Marg, Bandra (E), Mumbai–400 051 E-Mail: tservices@indianoil.co.in OR tech_services@indianoil.co.in