

SERVO HMT GREASE

GRADES AVAILABLE – SERVO HMT GREASE

DESCRIPTION

Servo HMT Grease is a premium quality lithium soap, multi-purpose automotive grease, with high drop point, good thermal and structural stability and also having resistance against water wash out. With its smooth structure and high degree of resistance against oxidation and rusting/corrosion it is an ideal product for all grease lubricated parts of HMT Tractors.

APPLICATION

Servo HMT Grease is recommended for grease lubricated parts of HMT Tractors.

PERFORMANCE BENEFITS

- Provides excellent resistance to structural and consistency changes, over wide range of temperatures but remains in place despite severe working or sustained shock impact
- Has excellent low and high temperature properties. It can be dispensed at low temperatures and will maintain adequate stay-put property at the higher temperatures encountered in service
- Resists effectively, water wash out in use, assuring adequate lubrication over extended service periods
- Provides resistance to oxidation, rust and corrosion.

PERFORMANCE STANDARDS

Servo HMT Grease meets IS:12203:1987 (Reaffirmed 1993)

MANUFACTURER’S APPROVAL

- Servo HMT Grease is approved as Genuine Grease for HMT Tractors

CHARACTERISTICS

GRADE	HMT Grease
Colour	Brown
Structure	Smooth
Soap Type	Lithium
Worked Penetration, @25°C, (60 Strokes)	220-250
Drop Point, °C Min.	180

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai – 400 051

E-Mail: tservices@indianoil.co.in OR tech_services@indianoil.co.in

