

SERVO GEAR HP 75W-90

GRADES AVAILABLE - SERVO GEAR HP 75W- 90

DESCRIPTION

Servo Gear HP 75W-90 is hypoid gear oil having long service life due to their extremely good oxidation stability. These oils are blended from selected base stocks and contain additives to provide extreme pressure, anti-rust-corrosion characteristics

APPLICATION

Servo Gear HP 75W-90 is recommended for hypoid, spiral bevel or worm gear transmission systems of cars, buses and highway trucks requiring EP type lubricants. This oil having very low pour point , can be used for power transmission unit of vehicles operating at sub zero temperature.

PERFORMANCE BENEFITS

- Servo Gear HP oils
- Satisfy the lubrication requirements of a wide variety of gears.
 - Provide protection against wear, due to good EP characteristics
 - Give long service life even under high temperature operation since it has excellent oxidation stability
 - Provide good protection against corrosion

PERFORMANCE STANDARDS

Servo Gear HP oils meets:

- API Service GL 4
- IS: 1118-1992
- UK Defence CS 3000A
- US military MIL-L-2105

CHARACTERISTICS

SAE GRADE	75W - 90
Kinematic Viscosity cSt @ 100°C	13.5-15.5
Viscosity Index, Min.	130
Flash point (COC), °C Min.	150
Pour Point, °C Max.	(-) 39

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR :

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai – 400 051

E-Mail: tsservices@indianoil.co.in OR tech_services@indianoil.co.in

