PRODUCT DATA SHEET

SERVO 4T SYNTH 10W-30

DESCRIPTION

Servo 4T Synth 10W-30 is blended with structurally modified base stock blended with synergistic additive system for outstanding detergency, dispersancy characteristics, antiwear and antioxidant properties, high viscosity index and low temperature flow properties. This delicately balanced composition provides and exceeds tough industry performance standards thus ensuring reliability, emission control, economy and endurance.

PERFORMANCE BENEFITS

- Selected synthetic base stocks impart inherent low temperature pumpability and excellent evaporation control in high speed, high temperature operation.
- Formulated with highly shear stable viscosity index modifiers which ensure viscosity control over extreme temperatures.
- Enhanced lubrication to help maintain maximum power and acceleration over the life of the engine.
- Optimized wet-clutch performance.
- Excellent low temperature flow characteristics to help minimize engine wear during start up.
- Potential improvement in fuel economy.
- Enhanced oil life and longer drain period.

CHARACTERISTICS

Kinematic Viscosity, cSt, @ 100°C	10 - 12
Viscosity Index, Min	150
Flash Point (COC), °C Min.	200
Pour Point, Deg C	(-) 30
TBN, mg KOH/gm	7.0 – 7.5
Sulphated Ash, % wt	0.80 - 0.85

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

E-Mail: tservices@indianoil.co.in OR tech_services@indianoil.co.in

Servo 4T Synth 10W-30 is recommended for on road high performance 4 Stroke Motor Cycle and Scooters particularly operating with wet clutch system.

IndianOil SERVO®

SPECIFICATIONS

Servo 4T Synth 10W-30 meets the performance requirement of API SM /JASO MA 2 specifications.