

SERVO POWER BRAKE ALT

GRADES AVAILABLE - SERVO POWER BRAKE ALT

DESCRIPTION

Servo Power Brake ALT is heavy duty hydraulic brake fluid which ensures long service life of the brake fluid and components of brake mechanism. It remains clear and uniform fluid under extreme cold climatic conditions, enabling satisfactory operation of brake systems.

This formulation is successfully adopted for clutch operation of Ashok Leyland tippers.

APPLICATION

Servo Power Brake ALT is recommended for use in clutch operation of Ashok Leyland tippers.

PERFORMANCE BENEFITS

Servo Power Brake ALT

- Ensure smooth clutch operation.
- Provides excellent protection against corrosion to iron, non-ferrous metals and zinc alloys
- Has longer service life, due to excellent oxidation stability

PERFORMANCE STANDARDS

Servo Power Brake ALT meets the following specification:

- SAE J 1703
- FMVSS 116.3
- IS:8654-1986

MANUFACTURERS APPROVAL

- Ashok Leyland Limited, Chennai

CHARACTERISTICS

Appearance	Clear Homogeneous red liquid
Equilibrium Reflex Boiling Point, °C Min.	205
Kinematic Viscosity, cSt	
@ (-) 40 °C, Max.	1500
@ 100 °C, Min.	1.5
pH Value	7.0-11.5

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai – 400 051

E-Mail: tservices@indianoil.co.in OR tech_services@indianoil.co.in

